Groundwater Plume Delineation Former Sabiston Landfill Site, Markham, Ontario



AGENDA

- History Council Resolution
- History Communications
- Evaluation of Water Quality Impacts
- Applicable Regulatory Requirements
- Why Additional Monitoring Required
- Groundwater Well Installation
- Next Steps
- Questions / Discussion

History – Council Resolution

- June 26, 2012 Council approved the following motion
 - Resolution (6): "That the following paragraph be referred to staff for a report to the General Committee in Fall, 2012 on an implementation plan and the impact of same on wildlife and vegetation:
 - That a Leachate Collection System be installed to intercept discharge to German Mills Creek and protect the Creek from contamination and where possible, this System should be installed and operated in a manner that minimizes disruption to existing wildlife and vegetation"
- November 20, 2012 Markham staff indicated the preferred alternative of leachate management is the establishment of a contamination attenuation zone (CAZ)

History – Council Resolution (Cont'd)

Nov 20, 2012 - Council approved the following recommendation:

Resolution (4): That the funding available in account 750-101-399-7028 "Settlers Park Landfill Site Management" of \$367,776 be reallocated to fund the additional rehabilitation works identified in the report;

Rehabilitation works identified in the report:

- Backup generator and motor
- Installation of additional groundwater monitoring wells (19 wells at 8 locations) to delineate the CAZ later reduced to 11 wells
- Groundwater plume delineation study
- Monitoring works by Tervita Corporation
- Installation of signage

History - Communications

- Meeting #2 (Sep 30, 2013) Liaison Committee requested additional information
- Meeting #3 (Oct 9, 2013) Liaison Committee requested monitoring results
- Memo #1 (Nov 6, 2013) Monitoring results
- Memo #2 (Nov 15, 2013) Comparison of Down-gradient Well parameters with Background Well
- Nov 21, 2013 Staff met with Mr. James
- Memo #3 (Dec 16, 2013) Answers to questions raised by Mr. James
- Dec 17, 2013 Staff met with Regional Councillor Li, Councillor Shore and Councillor Burke
- Dec 18, 2013 Councillor Shore met with Mr. James and Ms. Seymour
- Memo #4 (Jan 15, 2014) Answers to additional questions raised by Mr. James and Councillor Shore

Evaluation of Water Quality Impacts


- Water quality samples collected since 2009
- Compared water quality samples
 - Background / up-gradient of the landfill (OW-7)
 - Within the landfill (OW-10)
 - Down-gradient of the landfill (OW-9, OW-11 and OW-12)

Results of monitoring program

- Landfill still producing leachate
- Groundwater quality down-gradient of the landfill impacted by the landfill leachate
- Higher concentrations of the leachate contaminants compared to background/up-gradient levels
- The level of contaminants of concerns exceed the Ontario Drinking Water Quality Standard (ODWQS)
 - arsenic, vinyl chloride, tri-chloroethene (TCE) and di-chloroethene (DCE)] at monitoring wells
 OW-11 & OW-12
- Unknown how far the groundwater impacts have migrated down-gradient of the site

Evaluation of Water Quality Impacts (Cont'd)

Figure shows direction of groundwater flow, monitor stations with the greatest number of -parameters at concentrations exceeding the ODWQS or PWQOs, and key health-related contaminants of concern.



Applicable Regulatory Requirements

- The water quality monitoring program at the Sabiston Landfill Site and any required remedial measures must be in compliance with the following regulatory requirements:
 - Ontario Water Resources Act (OWRA) and Safe Drinking Water Act (SDWA)
 - Ontario Drinking Water Quality Standards (ODWQS)
 - Provincial Water Quality Objectives (PWQOs)
 - Ontario Environmental Protection Act (OEPA)
 - O. Reg. 153/04 Soil, Groundwater and Sediment Site Condition Standards (SCS)
 - O. Reg. 232/98 Landfill Standards Guideline
 - Reasonable Use Concept (RUC) Policy Ministry of the Environment
 - Canadian Fisheries Act

Why Additional Monitoring Required

- Determination full extent of leachate impacts
- Assess if mitigation measures are required
- Typical process in brownfield site investigation continues until the boundaries of the contamination plume are identified
- Gaps in existing monitoring: depth and location (down-gradient)
- Risk to down-gradient receivers
- Continue to meet applicable regulatory requirements


Groundwater Well Installation

- Installation of 11 new monitoring wells at 8 locations
 - Assess groundwater conditions down-gradient and in the deeper aquifer
- Sensitive to protection of the natural habitat:
 - Proposed in grassed areas (no trees or shrubs clearing)
 - Installation to take place outside of ground bird nesting for period of approx.
 2-3 weeks
 - Work will be completed in accordance with requirements of the Toronto and Region Conservation Authority (TRCA) and Ministry of Natural Resources (MNR)
 - Installation of wells will have no insignificant impact on the surrounding natural environment
- Installation work will be monitored by AMEC & Biologist from Dillon Consulting in accordance with the established Environmental Monitoring Management Plan (EMMP)
- Deadline to complete installation is April 1st 2014 per MNR permit

10

Groundwater Well Installation (Cont'd)

(Location Map)



Groundwater Well Installations (Cont'd)



Next Steps

- February 3, 2014 Status update to General Committee
- Communication to public
- Complete additional well installations prior to Permit expiry
 - April 1, 2014
- Report results of additional monitoring after one-year installation to Council and Liaison Committee

Background

Typical Schematic of Water Quality Impacts at Landfill Sites

